



NEW! Thermo Scientific Sorvall LYNX
Superspeed Centrifuge Series



performance simplified
at every turn

Thermo
SCIENTIFIC

Superspeed centrifugation simplified at every turn

Introducing the NEW! Thermo Scientific™ Sorvall™ LYNX superspeed centrifuge series, featuring powerful technologies with breakthrough simplicity.

Multiple users. A variety of processing requirements. A range of user experience. To overcome these everyday challenges of a shared laboratory setting choose the NEW! Thermo Scientific Sorvall LYNX superspeed centrifuge. The result? Productivity, safety, and reliability simplified.



Push-button security and application flexibility
Auto-Lock™ rotor exchange



Immediate rotor detection and programming
Auto-ID instant rotor identification



Improved ergonomics and performance
Fiberlite™ carbon fiber rotors



One-handed certified¹ sample protection
ClickSeal™ biocontainment lids

¹ Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK.

Exceptional performance meeting evolving application needs, from academic research to production facilities, with up to 100,605 x g, and up to 6 Liters capacity.

Versatile, high-throughput sample processing from 6 x 1 L bottles, to 40 x 50 mL conical tubes, to 24 microplates per run. Save time and ensure sample integrity with fast acceleration and deceleration rates, combined with smooth runs at all speeds.

Built-in safety and efficiency

- Rotor innovations — from Auto-Lock rotor exchange, to Auto-ID instant rotor identification, to speed handles on each rotor lid — shorten run set-up time while providing peace-of-mind that the rotor is secure
- Lightweight, corrosion-resistant Fiberlite carbon fiber rotors, including the new Fiberlite LEX designs, improve ergonomics and performance
- Touchscreen interface with bright, highly visible, and durable display simplifies run set-up while providing on-board training and access controls, such as user login with password protection
- Compact, non-bolt down design, automatic door opening, and an integrated surface work space optimize everyday centrifuge use

Proven reliability with robust design for consistent results and maximum uptime, year after year.



Performance simplified at every turn



Secure, trouble-free rotor installation and removal in as little as 3 seconds

Auto-Lock Rotor Exchange

Secure, push-button rotor exchange in as little as 3 seconds delivers:

- Improved safety and confidence that the rotor is automatically and securely locked and will not loosen during a run
- Trouble-free rotor installation and removal
 - No tools are required
 - The rotor locks itself to the centrifuge, eliminating the need for hand-tightening
- Flexibility to quickly change rotors and applications, matching the needs of your laboratory — today and in the future

Auto-ID Instant Rotor Identification

Immediate identification of a rotor when secured in the centrifuge chamber, with rotor specifications automatically loaded into the centrifuge parameters:

- Shortens run set-up time by eliminating the need to find and set rotor codes
- Eliminates over-speed risk, reduces error messages, and improves centrifuge, sample, and operator safety

Auto-ID instant rotor identification improves safety, saves time, and protects the integrity of your samples



1. Place rotor into the centrifuge chamber



2. Rotor is immediately detected and its parameters are loaded



3. Confirm settings and begin run



Innovative speed handles make tightening the lid safer while also simplifying lid removal



Thermo Scientific BIOFlex HC rotor supports up to 40 x 50 mL conical tubes, 96 x 15 mL conical tubes, 24 microplates, and over 35 other tube styles with dozens of adapters for research flexibility

Extensive Rotor Portfolio

Supports multiple users and evolving research needs — from microtubes up to 1 L bottles.

- **Fiberlite Carbon Fiber Rotors:** Simply lighter, more secure investment
 - Lightweight carbon fiber and innovative construction allow unique rotor designs not possible with metal
 - Corrosion- and fatigue-resistance secures the rotor's structural integrity for unequalled durability
 - Backed by a 15-year warranty²
- **Swinging Bucket Rotors:** Versatility and expanded capacity at high RCF with dozens of adapters for research flexibility
- **Fixed Angle Rotors:** Address specific protocol requirements with a range of specialty rotors, from dedicated conical tube rotors, to RCFs up to 100,605 x g
- **Continuous Flow/Zonal Rotors:** Scale-up flexibility from superspeed applications to harvesting and clarification

² Subject to Thermo Fisher Scientific's standard limited warranty. See thermoscientific.com or your sales representative for details.



Operation simplified at every turn

Touchscreen Interface

Simple and quick run set-up with a large, bright, interactive touchscreen for all centrifuge functions and durable for use run after run, year after year.

Plus the additional power of:

- Create up to 120 programs with alpha-numeric naming for easy access
- In-use training with on-board tutorial videos and a quick-start manual
- Integrated rotor calculator for simplifying protocol modifications and transfers
- Operator and run logging and reporting to assist with GMP/GLP compliance
- Convenient virtual touchscreen keyboard for direct input of program parameters
- Highly visible backlit display of set and actual run conditions, enlarged during the run for clear visibility — even from across the lab
- Multilingual instructions, including English, German, French, Spanish, Chinese, Japanese, and Portuguese, on programming, run conditions, alerts, and service messages
- User access control with optional password protection, ideal for multi-user environments



Glove-friendly touchscreen interface




Simple, quick run set-up and monitoring



Easily set current parameters and monitor centrifuge status

The Thermo Scientific Sorvall LYNX superspeed centrifuge series is available in two models



Choose between the **Sorvall LYNX 4000** centrifuge for 4 L capacity and performance up to 68,905 x g, and the **Sorvall LYNX 6000** centrifuge for 6 L capacity with:

- RCF up to 100,605 x g with broad rotor portfolio supporting higher performance and continuous flow/zonal capability
- Additional energy efficiency settings with Smart Vacuum
- Expanded levels of biosafety with an optional HEPA filter

Safety simplified at every turn



Lightweight rotors with speed handles



Foot space for better rotor placement ergonomics

Ergonomics and Safety

Effortless loading and unloading with optimal working height of 860 mm, an integrated surface work space, and front design with foot space allowing a closer position to the centrifuge.

- Easier and safer lifting and carrying of rotors with new speed handles, further enhanced with lightweight Fiberlite rotors
- Latest global safety standards without the need to bolt down the instrument to the floor, greatly simplifying installation and flexibility to relocate within a facility
- Quiet performance (<59 dBA) provides a safe and reduced stress environment
- Centrifuge door opens fully and automatically – even with full hands – by using the door-open bar mounted on front of the centrifuge
- Auto-Lock rotor exchange with Auto-ID instant rotor identification simplifies run set-up and eliminates the worry of overspeeding or rotor accidents

Secure Investment

- Outstanding imbalance-tolerant drive improves system reliability and longevity
- Robust design supported by a 1-year unit warranty, 3-year drive warranty, 5-year refrigeration warranty, and comprehensive 15-year Fiberlite carbon fiber rotor warranty²
- Protect your investment with our complete portfolio of customized, integrated, and innovative services and support solutions

GMP/GLP Data Management

- Simplified quality control and record keeping
- On-board and downloadable run logging of user, run conditions, and error messages
- Electronic signatures for runs with user log-in and password protection



USB port for downloading run data

² Subject to Thermo Fisher Scientific's standard limited warranty. See thermoscientific.com or your sales representative for details.

Resource Efficiency and Sustainability

- **Energy use options:** Choose sleep mode settings for increased energy savings
- **Smart Vacuum:** Address performance and efficiency requirements with our partial air system, which partially evacuates the rotor chamber and reduces the power needed in a typical run (*in the Sorvall LYNX 6000 only*)
- **Power factor corrector module:** Electronics designed for optimized interface with supply power system
- **Carbon fiber rotors:** Reduce capital investment and eliminate unnecessary equipment disposal issues with longer lifetime of Fiberlite rotors — backed by a 15-year warranty²
- **Compliant with global environmental standards:** RoHS (Restriction of Hazardous Substances) Directive and WEEE (Waste Electrical and Electronic) Directive 2002/96/EC

Applications simplified at every turn


The extensive rotor portfolio for the Sorvall LYNX superspeed centrifuge series supports labware from microplates, to microtubes, to 1 Liter bottles — providing applications flexibility for years to come, even as your lab's research focus evolves.

Innovative Rotor Convenience

- Accelerate and simplify rotor lid tightening, ensuring lid is properly attached with new speed handles
- Store rotor lid with on-board lid holder

Thermo Scientific rotors are available for a wide range of processing needs —

Cellular Biology • Diagnostic and Clinical Biology • Genomics and Molecular Biology • Proteomics • Virus and Nanotechnology • Research and Drug Discovery • Bioprocessing






Thermo Scientific Fiberlite LEX Rotors

The next generation of high capacity Fiberlite rotors, the Fiberlite LEX rotor series further advances carbon fiber design and is now available in 6 Liter capacity. These rotors combine:

- **Superior ergonomics:** The lightest of their kind³, with improved ergonomics for everyday ease of handling
- **Exceptional performance:** Achieve outstanding RCF performance for enhanced productivity — up to 17,670 x g with the Fiberlite F9-6x1000 LEX rotor
- **Enhanced safety:** From lightweight design and lifting handles, to biocontainment technology and certifications, these rotors provide multiple levels of laboratory and operator protection to enhance safety without compromising functionality or convenience

³ Based on a comparison with manufacturers' published specifications.



Rotor specifications

Category	Cat. No.	Rotor	Description	Maximum Capacity	Sample Containment
Swinging Bucket Rotors	75003000	BIOFlex HC 	Process over 35 tube styles from microtubes to 1 L bottles, plus conical tubes, microplates, tissue culture flasks, and blood bags	4 x 1000 mL 40 x 50 mL conical 24 microplates	
	75003002	BIOFlex HS 	Versatility of adapter options supporting more than 30 tube types from microtubes to conical tubes to 400 mL bottles	4 x 400 mL 4 x 250 mL conical	
	75003010	TH13-6x50 	Novel design for round or conical tubes, accommodating gradient separations or pelleting directly to the bottom of the tube	6 x 50 mL round 6 x 50 mL conical 6 x 15 mL conical	
Fixed Angle High Capacity Rotors	096-061075	Fiberlite F9-6x1000 LEX 	Process 6 Liters per run in lighter weight Fiberlite LEX design for large volume or bioprocessing or the flexibility of adapters for labware from 1.5 mL to 500 mL	6 x 1000 mL	
	096-041075	Fiberlite F10-4x1000 LEX 	Support occasional or lower volume bioprocessing in lighter weight Fiberlite LEX design and the flexibility of adapters for tubes from 1.5 mL to 500 mL	4 x 1000 mL	
	096-062375	Fiberlite F12-6x500 LEX 	Run popular 500 mL bottles to over 24,400 x g, with adapters available for smaller bottles	6 x 500 mL	
	096-062075	Fiberlite F14-6x250y 	Ideal for tissue homogenates, or smaller volume yeast or bacterial culture separations in up to 250 mL bottles	6 x 250 mL	
Fixed Angle High Speed Conical Rotors	096-145075	Fiberlite F14-14x50cy 	Dedicated solution for 50 mL conical tubes, with adapters for 15 mL or other tubes, for pelleting cells, tissue homogenates, or subcellular separations	14 x 50 mL conical	
	75003004	A21-24x15c 	Dedicated solution for 15 mL conical tubes for subcellular separations and fractionations	24 x 15 mL conical	
Fixed Angle High Speed Rotors	096-124375	Fiberlite F20-12x50 LEX 	Lighter weight Fiberlite LEX design for subcellular separations using Oak Ridge tubes	12 x 50 mL	
	096-084275	Fiberlite F21-8x50y 	50 mL 34° angle rotor for subcellular separations	8 x 50 mL	
	75003005	A22-24x16 	Support 16 mL tubes for subcellular separations	24 x 16 mL	
	75003006	A23-6x100 	Achieve 100 mL tubes capacity or the versatility of adapters for smaller tubes	6 x 100 mL	
Fixed Angle Highest RCF Performance Rotors	096-484075	Fiberlite F23-48x1.5 	Combine high g-force and high capacity of 1.5 mL microtubes	48 x 1.5 mL	
	75003007	A27-6x50 	Maintain lowest sample temperatures at all speeds	6 x 50 mL	
	75003008	A27-8x50 	For virus, proteomics, and subcellular particle separations in a modernized Thermo Scientific SS-34 rotor design	8 x 50 mL	
	75003009	T29-8x50 	Realize new level of high g-force (up to 100,605 x g) in a superspeed	8 x 50 mL	
Continuous Flow/Zonal Rotors	75003012	TCF-20 	Support bioprocessing or separation of large volumes with very low solids content	1350 mL	
	75003013	TCF-20 Zonal 	Achieve high g-force for large volume gradient separations	1350 mL	

 Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK.

	Sorvall LYNX 6000 Superspeed Centrifuge			Sorvall LYNX 4000 Superspeed Centrifuge			
	Rmax (mm)	Maximum Speed	Maximum RCF	K Factor	Maximum Speed	Maximum RCF	K Factor
	209	5,500 rpm	7,068 x g	5,522	5,500 rpm	7,068 x g	5,522
	183	7,000 rpm	10,025 x g	4,889	7,000 rpm	10,025 x g	4,869
	157	13,100 rpm	30,314 x g	1,503	13,100 rpm ⁴	30,314 x g	1,503
	194	9,000 rpm	17,568 x g	3,415			
	167	10,500 rpm	20,584 x g	4,268	10,500 rpm	20,584 x g	4,268
	152	12,000 rpm	24,471 x g	2,302	12,000 rpm	24,471 x g	2,302
	138	14,000 rpm	30,240 x g	1,699	14,000 rpm	30,240 x g	1,699
	154	14,000 rpm	33,746 x g	798	13,000 rpm	29,097 x g	925
Outer Row	122	21,500 rpm ⁴	63,049 x g	379	19,500 rpm ⁴	51,865 x g	461
Inner Row	122	21,500 rpm ⁴	63,049 x g	558	19,500 rpm ⁴	51,865 x g	679
	115	20,000 rpm	51,428 x g	455	18,000 rpm	41,657 x g	562
	107	20,000 rpm	47,850 x g	744	18,000 rpm ⁴	38,759 x g	919
Outer Row	111	22,000 rpm	60,063 x g	377	22,000 rpm ⁴	60,063 x g	377
Inner Row	111	22,000 rpm	60,063 x g	547	22,000 rpm ⁴	60,063 x g	547
	97	23,500 rpm	62,976 x g	503	21,000 rpm	50,290 x g	630
	97	23,000 rpm	57,368 x g	199	18,500 rpm	37,116 x g	307
	97	27,000 rpm ⁴	79,057 x g	485	24,000 rpm ⁴	62,465 x g	613
	107	27,000 rpm ⁴	87,207 x g	408	24,000 rpm ⁴	68,905 x g	517
	107	29,000 rpm ⁴	100,605 x g	354	24,000 rpm ⁴	68,905 x g	517
	96	20,000 rpm ⁴	42,931 x g	826			
	96	20,000 rpm ⁴	42,931 x g	826			

⁴ 4 °C cannot be achieved at top speed. Please refer to the rotor manual for published specifications.

Biocontainment Security

- To enhance containment of biohazardous samples, superspeed rotors certified by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK are noted by ☠️
- In case of tube or bottle failure, a volume of fluid is contained in a special curved containment annulus at the top of most fixed angle rotors
- Thermo Scientific Sorvall LYNX 6000 centrifuges with HEPA filters provide an additional level of safety in case of tube or bottle failure



Fiberlite F9-6x1000 LEX rotor:
New lighter weight LEX design supports 6 x 1 L bottles with the versatility of tube adapters for 1.5 mL microtubes to 500 mL bottles



BIOFlex HC swinging bucket rotor with optional ClickSeal lids:
Spin more than 35 tube styles with dozens of adapters for research flexibility

Rotor adapters

for Thermo Scientific BIOFlex HC swinging bucket rotor

Cat. No.	Description	Rotor Capacity (places x volume, mL)	Max Tube Dimensions (Ø x L, mm)
Rotor			
75003000	BIOFlex HC Swinging Bucket Rotor	4 x 1000	
75007309	ClickSeal Biocontainment Lids for BIOFlex HC Buckets (set of 4) 		
75007304	BIOLink Adapter for BIOFlex HC Buckets (set of 4)		
Adapters for BIOFlex HC Rotor (sets of 4)			
75007301	1 1000 mL Polypropylene Wide-Mouth Bio-Bottle (75007300)	4 x 1000	126 x 140
75007304	2 750 mL Polypropylene Wide-Mouth Bio-Bottle	4 x 750	98 x 133
75004253	3 500 mL Nalgene Oak Ridge Bottle	4 x 500	70 x 160
75007302	4 500 mL Corning™ Conical Bottle	4 x 500	98 x 133
75005392	5 250 mL Nalgene Wide-Mouth Conical Bottle	4 x 250	62 x 145
75005392	5 250 mL Corning Conical Bottle or 200 mL Nunc Bottle or 175 mL Nalgene Conical Bottle	4 x 250	62 x 145
75007305	6 250 mL Nalgene Oak Ridge Bottle	8 x 250	62 x 130
75007305 + BD 352090	6 225 mL BD Falcon™ Conical Bottle	8 x 225	62 x 130
75007305 + Nunc 377585	6 200 mL Nunc Conical Bottle	8 x 200	62.5 x 139
75007305 + Nalgene DS3126-0175	6 175 mL Nalgene Wide-Mouth Conical Bottle	8 x 175	62 x 130
75003674	7 50 mL Conical Tissue Culture Tube	40 x 50	30 x 120
75004255	8 50 mL Double Biocontainment Vessel for 50 mL Conical Tube	20 x 50	29.5 x 120
75004252	9 50 mL Nalgene Oak Ridge Tube	48 x 50	29.5 x 120
75007306	10 15 mL Conical Tissue Culture Tube	96 x 15	17.5 x 121
75003672	11 10 mL Blood Collection Tube or Corex™/Kimble™ Tube	148 x 10	17 x 110
75003671	12 5/7 mL Blood Collection Tube (BD Vacutainer™)	196 x 5/7	14 x 110
75003709	13 4.5/6 mL Blood Collection Tube (Greiner™)	164 x 4.5/6	14 x 110
75007303	14 Microplate Carriers	4 x 6 Standard or 4 x 2 Deep-Well	86 x 128
75003829	15 Small Blood Bag/Cell Culture Bags	4 x 2 Bags	
Adapters for BIOFlex HC Rotor (sets of 4)⁵			
75003713	16 100 mL Round Bottom Open-Top Tube	8 x 100	62.5 x 139
75003824	17 50 mL Conical or Skirted Tube	20 x 50	29.5 x 120
75003716	18 25 mL Universal Conical or Skirted Tube	28 x 25	29.5 x 120
75003718	19 16 mL Nalgene Round Bottom Tube	48 x 16	18 x 134
75003719	20 15 mL Blood Collection Tube	32 x 15	17 x 125
75003724	21 5 mL RIA or Round Bottom Tube (without cap)	148 x 5	13 x 116
75003733	22 1.5/2.0 mL Conical or Round Bottom Microtube	192 x 1.5/2.0	11 x 50
75008383	23 T-75 Nunc Easy Flask	4 x T-75	
75008384	24 T-25 Nunc Easy Flask	8 x T-25	

⁵ Must be used with a BIOLink adapter (75007304)



Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK.



1



2



3



4



5



6



7



8



9



10



11



12



13



14



15



16



17



18



19



20



21



22



23



24



Rotor adapters

for Thermo Scientific BIOFlex HS swinging bucket rotor

Cat. No.	Description	Rotor Capacity (places x volume, mL)	Max Tube Dimensions (Ø x L, mm)
Rotor			
75003002	BIOFlex HS Swinging Bucket Rotor	4 x 400	
75003656	ClickSeal Biocontainment Lids for BIOFlex HS Buckets (set of 4) 		
Adapters for BIOFlex HS Rotor (sets of 4)			
No adapter needed	25 400 mL Polypropylene Bio-Bottle (75007585)	4 x 400	80 x 125
75004258	26 250 mL Nalgene Wide-Mouth Conical Bottle	4 x 250	62 x 135
75004257	27 250 mL Nalgene Oak Ridge Bottle	4 x 250	62 x 135
75004257	27 225 mL BD Falcon Conical Bottle	4 x 225	62 x 130
75004258	26 200 mL Nunc PPCO Conical Bottle	4 x 200	62 x 125
75004258	26 175 mL Nalgene Wide Mouth Conical Bottle	4 x 175	62 x 125
75003708	28 100 mL Round Bottom Open-Top Tube	4 x 100	45 x 117
75003707	29 50 mL DIN Round Bottom Tube	12 x 50	34.5 x 105
75004259	30 50 mL Double Biocontainment Vessels for 50 mL Conical Tube	8 x 50	29.5 x 116
75005393	31 50 mL Conical Tissue Culture Tube	12 x 50	29.5 x 116
75003683	32 50 mL Conical Tissue Culture Tube	16 x 50	29.5 x 116
75003799	33 50 mL Nalgene Oak Ridge Tube	16 x 50	28.5 x 114
75003703	34 30 mL DIN Round/Flat Bottom Tube	20 x 30	25.5 x 108
75003706	35 20/25 mL Universal Round Bottom Tube	12 x 20	25 x 110
75003798	36 16 mL Nalgene Round Bottom Tube	28 x 16	18 x 112
75005394	37 15 mL Conical Tissue Culture Tube	36 x 15	17 x 121
75003704	38 15 mL Round Bottom Tube (Sarstedt™)	40 x 15	17 x 105
75003794	39 15 mL Blood Collection Tube (17 x 125 mm)	16 x 15	15.5 x 131
75003681	40 10/15 mL Corex/Kimble Tube or 10 mL Blood Collection Tube (BD Vacutainer/Vacurette™)	56 x 10/15	17 x 113
75003680	41 5/7 mL Blood Collection Tube (BD Vacutainer)	76 x 5/7	13 x 110
75003825	42 4.5/6 mL Blood Collection Tube (Greiner)	64 x 4.5/6	13 x 110
75003793	43 3/5 mL RIA or Round Bottom Tube (without cap)	76 x 3/5	11 x 110
75003700	44 1.5/2 mL Conical or Round Bottom Microtube	136 x 1.5/2	11 x 45



Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK.



25



26



27



28



29



30



31



32



33



34



35



36



37



38



39



40



41



42



43



44



Rotor selection simplified at every turn

Category	Cat. No.	Rotor	1000 mL (A)	500 mL (B)	500 mL Conical (C)	250 mL (D)	250 mL Conical (E)	175 mL Conical (F)	100 mL (G)	80 mL	50 mL	50 mL Conical (H)	30 mL (I)	16 mL (J)	15 mL Conical (K)	12 mL	10 mL (L)	7 mL	5 mL	4 mL Microtubes (M)	3 mL	2.0 Microtubes	1.5 Microtubes	1.0 CAB Tube	Microplates (N)	Tissue Culture Flask (O)	Filtration Kits	Blood Tubes (P)	Blood Bags — small
Swinging Bucket Rotors	75003000	BIOFlex HC	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	75003002	BIOFlex HS				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓	✓	
	75003010	TH13-6x50									✓	✓	✓		✓														
Fixed Angle High Capacity Rotors	096-061075	Fiberlite F9-6x1000 LEX	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓		✓			✓		✓	✓					✓	
	096-041075	Fiberlite F10-4x1000 LEX	✓	✓	✓	✓	✓		✓		✓	✓	✓	✓	✓		✓			✓		✓	✓					✓	
	096-062375	Fiberlite F12-6x500 LEX		✓		✓	✓		✓		✓	✓	✓	✓	✓		✓											✓	
	096-062075	Fiberlite F14-6x250y				✓			✓		✓	✓	✓	✓	✓	✓	✓											✓	
Fixed Angle High Speed Conical Rotors	096-145075	Fiberlite F14-14x50cy									✓	✓	✓	✓	✓		✓										✓	✓	
	75003004	A21-24x15c													✓												✓		
Fixed Angle High Speed Rotors	096-124375	Fiberlite F20-12x50 LEX									✓		✓	✓	✓		✓											✓	
	096-084275	Fiberlite F21-8x50y									✓		✓	✓	✓		✓											✓	
	75003005	A22-24x16													✓			✓	✓		✓	✓							
	75003006	A23-6x100							✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓					✓	
Fixed Angle High RCF Performance Rotors	096-484075	Fiberlite F23-48x1.5																					✓						
	75003007	A27-6x50									✓		✓	✓		✓	✓	✓		✓	✓	✓		✓				✓	
	75003008	A27-8x50									✓		✓	✓		✓	✓	✓		✓	✓	✓		✓				✓	
	75003009	T29-8x50									✓		✓	✓		✓	✓	✓		✓	✓	✓		✓				✓	



A. 1000 mL



B. 500 mL



C. 500 mL Conical



D. 250 mL



E. 250 mL Conical



F. 175 mL Conical



G. 100 mL



H. 50 mL Conical



I. 30 mL



J. 16 mL



K. 15 mL Conical



L. 10 mL



M. 4 mL



N. Microplates



O. Tissue Culture Flask



P. Blood Tubes

Optimize the Performance of Your Centrifuge

It's simple. From 1 L bottles, to 15 and 50 mL conical tubes, to microplates and tissue culture flasks, the versatile selection of **Thermo Scientific™ Nalgene™** and **Nunc™ centrifugation products** work seamlessly with your complete centrifuge and rotor system, bringing together best-in-class quality and performance.



Specifications and ordering information

Specifications	Thermo Scientific Sorvall LYNX 6000 Superspeed Centrifuge		Thermo Scientific Sorvall LYNX 4000 Superspeed Centrifuge	
Maximum Capacity	Fixed Angle Rotor: 6 Liters (6 x 1000) 9,000 rpm, 17,568 x g	Swinging Bucket Rotor: 4 Liters (4 x 1000) 24 microplates, 40 x 50 mL or 96 x 15 mL conical tubes 5,500 rpm, 7,068 x g	Fixed Angle Rotor: 4 Liters (4 x 1000) 10,500 rpm, 20,584 x g	Swinging Bucket Rotor: 4 Liters (4 x 1000) 24 microplates, 40 x 50 mL or 96 x 15 mL conical tubes 5,500 rpm, 7,068 x g
Maximum Speed	29,000 rpm		24,000 rpm	
Maximum RCF	100,605 x g (with T29-8x50 rotor)		68,905 x g (with A27-8x50 rotor)	
Rotor Locking System	Auto-Lock		Auto-Lock	
Rotor Identification	Auto-ID Instant, Automatic		Auto-ID Instant, Automatic	
Drive System	High Torque Brushless		High Torque Brushless	
Imbalance Tolerance	5% of Opposing Loads ⁶		5% of Opposing Loads ⁶	
Partial Vacuum System	Smart Vacuum		No Vacuum	
HEPA Filter	Optional		Not Available	
Green Technology	Green Mode, Smart Vacuum		Green Mode	
Control	Touchscreen Interface		Touchscreen Interface	
Accel/Decel Profiles	9 Accel, 10 Decel		9 Accel, 10 Decel	
Speed Range	Minimum 500 rpm, Maximum 29,000 rpm		Minimum 500 rpm, Maximum 24,000 rpm	
Speed Control Accuracy	± 25 rpm		± 25 rpm	
Run Time	99 hours, hold		99 hours, hold	
Pre-Cooling Function	Yes		Yes	
Temperature Set Range	-20 to +40 °C		-10 to +40 °C	
Temperature Accuracy	± 2 °C		± 2 °C	
ACE Integrator (w2t)	Yes		Yes	
Continuous Flow	Yes		No	
Other Functions	Multilingual Selection, Rotor Calculator, On-Board Training Videos, User Logging, User Lock-Out, Automatic Door Opening, Rotor Speed Handle		Multilingual Selection, Rotor Calculator, On-Board Training Videos, User Logging, User Lock-Out, Automatic Door Opening, Rotor Speed Handle	
Instrument Bolt Down	Not Required, Optional Seismic Bolt Down		Not Required, Optional Seismic Bolt Down	
Dimensions (H x D x W)	930 x 805 x 700 mm/36.6 x 31.7 x 27.6 in		930 x 805 x 700 mm/36.6 x 31.7 x 27.6 in	
Work Height of Top Deck	860 mm/33.9 in		860 mm/33.9 in	
Weight	293 kg/644 lb (Cat. No. 75006590) and 309 kg/680 lb (Cat. No. 75006591)		283 kg/622 lb (Cat. No. 75006580) and 299 kg/658 lb (Cat. No. 75006581)	
Heat Output	<2.0 kW		<3.2 kW	
Noise	<59 dBA		<59 dBA	
Certification	cULus ⁷ , CE, IEC 61010-2-020 2nd Ed. or later, ROHS, WEEE		cULus ⁷ , CE, IEC 61010-2-020 2nd Ed. or later, ROHS, WEEE	
Warranty²	1 Yr Unit, 3 Yrs Drive, 5 Yrs Refrigeration		1 Yr Unit, 3 Yrs Drive, 5 Yrs Refrigeration	

² Subject to Thermo Fisher Scientific's standard limited warranty. See thermoscientific.com or your sales representative for details.

⁶ Fiberlite F9-6x1000 rotor imbalance is 25 gr; BIOFlex HC rotor imbalance is 20 gr (opposing loads).

⁷ Applies to Cat. No. 75006590 and 75006580 only.

Ordering Information

Cat. No.	Description
75006590	Sorvall LYNX 6000 Superspeed Centrifuge, 200–240 V, 50/60 Hz, 30 A, Single-phase
75006591	Sorvall LYNX 6000 Superspeed Centrifuge, 380–400 V, 50/60 Hz, 16 A, 3-phase
75006580	Sorvall LYNX 4000 Superspeed Centrifuge, 200–240 V, 50/60 Hz, 30 A, Single-phase
75006581	Sorvall LYNX 4000 Superspeed Centrifuge, 380–400 V, 50/60 Hz, 16 A, 3-phase
75000011	HEPA Filter (for use with Cat. No. 75006590 and 75006591 only)



Experience our new superspeed centrifuges in action at
thermoscientific.com/lynxsuperspeed

© 2012, 2013 Thermo Fisher Scientific Inc. All rights reserved. Corning and Corex are registered trademarks of Corning. BD Falcon and BD Vacutainer are registered trademarks of Becton, Dickinson and Company. Kimble is a registered trademark of Kimble Chase. Greiner and Vacuette are registered trademarks of Greiner. Sarstedt is a registered trademark of Sarstedt, Walter DBA. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300

Austria +43 1 801 40 0

Belgium +32 53 73 42 41

China +86 21 6865 4588 or

+86 10 8419 3588

France +33 2 2803 2180

Germany national toll free 0800 1 536 376

Germany international +49 6184 90 6000

India toll free 1800 22 8374

India +91 22 6716 2200

Italy +39 02 95059 554

Japan +81 45 453 9220

Netherlands +31 76 579 55 55

New Zealand +64 9 980 6700

Nordic/Baltic/CIS countries

+358 9 329 10200

Russia +7 812 703 42 15

Spain/Portugal +34 93 223 09 18

Switzerland +41 44 454 12 22

UK/Ireland +44 870 609 9203

USA/Canada +1 866 984 3766

Other Asian countries +852 2885 4613

Countries not listed +49 6184 90 6000

Thermo
SCIENTIFIC

Part of Thermo Fisher Scientific